



CKE Number	Maximum Ratings (TA=125°C)				Characteristics (TA=25°C)					
	Max. Allowable Voltage		Surge Current 8/20us(A)	Energy Absorption (10/1000us) (J)	Max. Clamping Voltage		Varistor Voltage (V)	Typical Capacitance pF(MHz)	Figure 129 Thickness	
	AC (V _{RMS})	DC(V)			(A)	(V)			T±0.0394 (inches)	T±1 (mm)
08CH180K	11	14	250	0.8	5	40	18(16-20)	3300	0.0591	1.5
08CH220K	14	18	250	1.0	5	46	22(20-24)	1750	0.0591	1.5
08CH270K	17	22	250	1.0	5	56	27(24-30)	1500	0.0591	1.5
08CH330K	20	26	250	1.2	5	67	33(30-36)	1200	0.0591	1.5
08CH390K	25	31	250	1.5	5	76	39(35-43)	820	0.0591	1.5
08CH470K	30	38	250	1.8	5	90	47(42-52)	660	0.0591	1.5
08CH560K	35	45	250	2.3	5	106	56(50-62)	530	0.0787	2.0
08CH680K	40	56	250	3.0	5	124	68(62-74)	360	0.0787	2.0
08CH820K	50	65	500	4.0	10	135	82(74-90)	250	0.0591	1.5
08CH101K	65	85	500	5.0	10	165	100(90-110)	225	0.0591	1.5
08CH121K	75	102	500	6.0	10	198	120(108-132)	200	0.0591	1.5
08CH151K	95	127	500	8.0	10	248	150(135-165)	150	0.0591	1.5
08CH181K	115	153	500	10.0	10	292	180(162-198)	110	0.0591	1.5
08CH201K	130	175	500	11.0	10	340	200(180-220)	100	0.0591	1.5
08CH221K	140	180	500	12.0	10	356	220(198-242)	94	0.0591	1.5
08CH241K	150	200	500	13.0	10	390	240(216-264)	86	0.0591	1.5
08CH271K	175	225	500	14.0	10	450	270(243-297)	76	0.0591	1.5
08CH301K	190	250	500	15.0	10	495	300(270-330)	64	0.0591	1.5
08CH331K	210	275	500	16.0	10	545	330(297-363)	52	0.0591	1.5
08CH361K	230	300	500	20.0	10	593	360(324-396)	45	0.0787	2.0
08CH391K	250	330	500	21.0	10	647	390(351-429)	42	0.0787	2.0
08CH431K	275	369	500	23.0	10	705	430(387-473)	39	0.0984	2.5
08CH471K	300	385	500	25.0	10	775	470(423-517)	35	0.0984	2.5

Consult Factory for MOQ.

Note: Parts are available on tape and reel in quantities of 1000 pieces per reel.

All parts are RoHS compliant